

# PROJEKT 08

Model 112.P.08.244.03.721 D/ surface black



spotlight  
LED | 1200 lm 3000 K



LED

DALI

IP20




5Y



- passive thermo management
- with LED 1200 lm
- colour temperature: 3000 K
- colour rendering index: CRI >90
- L90 / B10 (50.000h)
- SDCM < 2
- net luminous flux: 960 lm
- total load: 14 W
- luminous efficacy: 68,6 lm/W
- rotationsymmetrical light distribution, flood
- beam angle: 45°
- LED power unit integrated in adapter, electronic (DALI), 220-240 V, 0/50/60 Hz
- dimmable
- dimming range: 100-0,5 %
- housing of die cast aluminium
- adapter of fibreglass reinforced thermoplastic
- microprismatic filter with very high rate of light transmission
- length: 221 mm, width: 84 mm, height: 182 mm
- rotatable 360°, 90° tiltable
- weight: 0,7 kg
- protection rating: IP20
- protection class I
- maximum ambient temperature: 35 °C
- certificates: manufactured according to DIN VDE 0711 / EN 60598

## Accessories



Anna Ostrowska

tel. +48 533 525 671

[a.ostrowska@projekt08.pl](mailto:a.ostrowska@projekt08.pl)

[www.projekt08.pl](http://www.projekt08.pl)