

# PROJEKT 08

Model 113.P.08.343.03.721 D black



spotlight  
LED | 3300 lm 3000 K


LED

DALI

IP20



5Y



- circuit selection is possible while adapter is inserted into the track
- passive thermo management
- with LED 3300 lm
- colour temperature: 3000 K
- colour rendering index: CRI >90
- L90 / B10 (50.000h)
- SDCM < 2
- net luminous flux: 2920 lm
- total load: 41 W
- luminous efficacy: 71,2 lm/W
- medium
- beam angle: 25 °
- LED power unit integrated in adapter, electronic (DALI)
- temperature-controlled LED circuit board (NTC)
- dimmable
- dimming range: 100-0,5 %
- housing of die cast aluminium
- adapter of fibreglass reinforced thermoplastic
- safety glass, clear
- length: 221 mm, width: 84 mm, height: 197 mm
- rotatable 360°, 90° tiltable (can be fixed)
- weight: 1,3 kg
- protection rating: IP20
- protection class I
- maximum ambient temperature: 35 °C
- certificates: manufactured according to DIN VDE 0711 / EN 60598

## Accessories



Anna Ostrowska  
tel. +48 533 525 671  
[a.ostrowska@projekt08.pl](mailto:a.ostrowska@projekt08.pl)  
[www.projekt08.pl](http://www.projekt08.pl)